PAT-NO:

JP409252931A

DOCUMENT-IDENTIFIER:

JP <u>09252931</u> A

TITLE:

CURTAIN FOR SHIELDING LIGHT

PUBN-DATE:

September 30, 1997

INVENTOR - INFORMATION:

NAME

HAGIWARA, KOSHIRO UCHIDA, TAKEHIKO

ASSIGNEE - INFORMATION:

NAME

COUNTRY

HAGIWARA KOSHIRO

N/A

APPL-NO:

JP08063995

APPL-DATE:

March 21, 1996

INT-CL (IPC): A47H023/08, A47H023/04, C23C014/20

ABSTRACT:

PROBLEM TO BE SOLVED: To provide a light curtain excellent in a light

shielding property, heat shielding property or the like without sacrificing the

decorative property of cloth itself of the curtain by pinching a synthetic

resin film formed with a metallic film between two cloths.

SOLUTION: A light shielding curtain has a biaxially stretched polyester film

- 3 formed with an aluminum evaporated film and pinched between resin made prints
- 1, 2, and hot melt adhesives 5, 6 having ethylene-vinyl acetate copolymer as

the main component are applied to the surface of the film 3 for adhesion.

Further, the clothe is selected from clothing fabrics like a drape, print and

plain cloth. A method for forming a metallic film on the surface of

- D. K.

the

synthetic resin film is preferably a vacuum vaporization method from an

econimical point of view. Also, aluminum is preferable for the metal of

metallic film from points of view of the operability, light shielding property,

economy or the like. The thickness of the metallic film is selected within

1-15μ m of the extent so that the transmission factor of the synthetic resin

film formed with the metallic film is less than 5%.

COPYRIGHT: (C) 1997, JPO